

JOKISCH MONOS ATOS C3P (Jokisch Monos Atos M16, 23)

Hydrocrack metalworking oil for severe metal processing.

Characteristics: Good compatibility towards sealing gaskets and coatings

APPLICATION

High performance metalworking oil for machining steel, titanium, copper and aluminum alloys.

Also suitable for the processing of medical implants made of stainless steel and titanium alloys.

CHARACTERISTICS

Chlorine and heavy metal-free processing oil with a high flash point and the following characteristics:

- Very good cooling and lubricating properties
- Good anti corrosion properties
- High EP-properties
- Very good resistance to aging
- Low foaming tendency
- Excellent compatibility with copper alloys

TECHNICAL SPECIFICATIONS

	UNIT	METHOD	-16-	-22-
Kin. viscosity at 40°C	mm ² /s	DIN 51 562	16	22
Density at 20°C	g/cm ³	ASTM D 4052	0,88	0,86
Flash point	°C	ASTM D 92	180	200

Diese Angaben stützen sich auf den neuesten Stand der Kenntnisse. Sie sollen das Produkt beschreiben und haben somit nicht die Bedeutung, bestimmte Eigenschaften zuzusichern. Eine Verbindlichkeit kann hieraus nicht hergeleitet werden.

STORAGE

Storage temperature: 5 – 40°C
Storage time: 36 months

Jokisch GmbH
Fabrik für Schmier- und Kühlmittelspezialitäten

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokisch-fluids.de | www.jokisch-fluids.de

