

TECHNICAL DATA SHEET

JOKISCH FOSIA CLEAN 165 (Jokisch Cold Degreaser L 100)

Hydrocarbon-based detergent with anti-corrosion properties.

APPLICATION

Degreaser that is used undiluted at cold degreasing in metal processing and is suitable for all materials.

Is preferably used in immersion baths for cleaning workpieces which have been processed with non-water-miscible cooling lubricants.

CHARACTERISTICS

Degreaser based on mixed paraffins with cleaning and corrosion protection additives. Free of halogen compounds, low in aromatics and low odor.

Reduces the pollution at the workplace through these properties.

After evaporation of the hydrocarbon, a light film remains as temporary corrosion protection on the workpieces.

The protection period, when stored indoors, is max. 1 week.

TECHNICAL SPECIFICATIONS

	UNIT	METHOD	JOKISCH FOSIA CLEAN 165
Kin. viscosity at 20°C	mm ² /s	DIN 53211/4	1,6
Density at 20°C	g/cm ³	DIN 51757	0,78
Flash point	°C	-	> 65

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this.

LAGERUNG

Storage temperature: 5 – 40°C
Storage time: 24 months

Jokisch GmbH
Fabrik für Schmier- und Kühlmittelspezialitäten

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokisch-fluids.de | www.jokisch-fluids.de

