

TECHNICAL DATA SHEET

JOKISCH FOSIA SKIM S.M (Jokisch Discscimmer)

Discscimmer removes tramp oil and floating contaminations, as a result bacteria formation is largely avoided.

Smell and steam development is significantly reduced for the user Anwender.

APPLICATION

1. The disc scimmer should only be attached to the coolant reservoir after the coolant was left for 2 hours or longer to ensure that the tramp oils had time to separate and have been deposited on the surface.
2. Attach the disc scimmer to the coolant reservoir so that the disc is submerged at a depth of 10 to 40 mm in to the liquid. The 2 joints give you a wide range of adjustment possibilities. The drain pipe with hose should always be sloped slightly downwards to ensure reliable skimming of the tramp oils. The collection container should have sufficiently large dimensions.
3. Either the machine can be switched on directly at the power supply or with the plug-in connector on the housing. You have the option of setting the voltage on the power supply in steps from 3 to 12 volts. The rotation speed increases as the voltage gets higher. We recommend to begin with level 6 (12 volts) when switching on, because the friction forces are still relatively high. After only a few rotations, the voltage and therefore the rotations per minute can be adjusted down to level 1 (3 volts), because the oil scimmer produces its best results at the slowest speed.
4. The period of use will depend largely on the volume of tramp oil. (It usually takes between 2 and 12 hours.) Longer operating times (e.g. at the weekend) are possible if you have provided a large enough collection container, so that inadvertent spilling is prevented.

SAFETY INSTRUCTION

Protect the plug-in mains adaptor (220 V) from being splashed with water. If possible, avoid the disc from becoming jammed. Do not touch the disc with your hand during operation. If there is a large quantity of floating foreign material (plastic shavings, etc.), blockages can occur, which may cause a larger quantity of coolant to be skimmed off or a blockage in the drain pipe. This can be avoided by making regular inspections and cleaning as required. Do not clean the disc with liquids containing solvents. CE mark present.

TECHNICAL SPECIFICATIONS



Disc diameter:	300mm
Power:	ca. 5 L/h
Rated voltage:	3-12V
Submersion depth:	10-100mm